



US007210544B2

(12) **United States Patent**
Kamen et al.

(10) **Patent No.:** **US 7,210,544 B2**
(45) **Date of Patent:** **May 1, 2007**

(54) **CONTROL OF A TRANSPORTER BASED ON ATTITUDE**

(75) Inventors: **Dean L. Kamen**, Bedford, NH (US);
Robert R. Ambrogi, Manchester, NH (US); **Richard Kurt Heinzmann**,
Francetown, NH (US)

(73) Assignee: **DEKA Products Limited Partnership**,
Manchester, NH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/617,598**

(22) Filed: **Jul. 11, 2003**

(65) **Prior Publication Data**
US 2004/0055795 A1 Mar. 25, 2004

Related U.S. Application Data

(60) Provisional application No. 60/395,589, filed on Jul. 12, 2002.

(51) **Int. Cl.**
B62D 57/00 (2006.01)
B62D 61/00 (2006.01)
B60G 17/00 (2006.01)

(52) **U.S. Cl.** **180/7.1**; 180/21; 180/218;
180/282; 280/5.502

(58) **Field of Classification Search** 180/282,
180/271, 7.1, 21, 218; 280/5.502–5.513
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

584,127 A 6/1897 Draullette et al.

849,270 A 4/1907 Schafer et al.
1,739,716 A 12/1929 Fisher
2,742,973 A 4/1956 Johannesen
3,145,797 A 8/1964 Taylor
3,260,324 A 7/1966 Suarez
3,283,398 A 11/1966 Andren
3,374,845 A 3/1968 Selwyn

(Continued)

FOREIGN PATENT DOCUMENTS

DE 2 048 593 5/1971

(Continued)

OTHER PUBLICATIONS

Kawaji, S., Stabilization of Unicycle Using Spinning Motion, *Denki Gakkai Ronbunshi, D*, vol. 107, Issue 1, Japan (1987), pp. 1-22.

(Continued)

Primary Examiner—Lesley D. Morris
Assistant Examiner—Marc A. Scharich

(74) *Attorney, Agent, or Firm*—Bromberg & Sunstein LLP

(57) **ABSTRACT**

A transporter for transporting a load over a surface. The transporter includes a support platform for supporting the load. The support platform is characterized by a fore-aft axis, a lateral axis, and an orientation with respect to the surface, the orientation referred to as an attitude. At least one ground-contacting element is flexibly coupled to the support platform in such a manner that the attitude of the support platform is capable of variation. One or more ground-contacting elements are driven by a motorized drive arrangement. A sensor module generates a signal characterizing the attitude of the support platform. Based on the attitude, a controller commands the motorized drive arrangement.

18 Claims, 4 Drawing Sheets

12

10

11

18

17

6

15

15

5

19

O

O

3

13

14

4

US 7,210,544 B2

Page 2

U.S. PATENT DOCUMENTS

3,399,742 A 9/1968 Malick
 3,446,304 A 5/1969 Alimanestiano
 3,450,219 A 6/1969 Fleming
 3,515,401 A 6/1970 Gross
 3,580,344 A 5/1971 Floyd
 3,596,298 A 8/1971 Durst, Jr.
 3,724,874 A 4/1973 Simpson
 3,860,264 A 1/1975 Douglas et al.
 3,872,945 A 3/1975 Hickman et al.
 3,952,822 A 4/1976 Udden et al.
 3,967,862 A 7/1976 Hunter et al.
 4,018,440 A 4/1977 Deutsch
 4,062,558 A 12/1977 Wasserman
 4,076,270 A 2/1978 Winchell
 4,088,199 A 5/1978 Trautwein
 4,094,372 A 6/1978 Notter
 4,109,741 A 8/1978 Gabriel
 4,111,445 A 9/1978 Haibeck
 4,151,892 A 5/1979 Francken
 4,222,449 A 9/1980 Feliz
 4,264,082 A 4/1981 Fouchey, Jr.
 4,266,627 A 5/1981 Lauber
 4,293,052 A 10/1981 Daswick et al.
 4,325,565 A 4/1982 Winchell
 4,354,569 A 10/1982 Eichholz
 4,363,493 A 12/1982 Veneklasen
 4,373,600 A 2/1983 Buschbom et al.
 4,375,840 A 3/1983 Campbell
 4,510,956 A 4/1985 King
 4,560,022 A 12/1985 Kassai
 4,566,707 A 1/1986 Nitzberg
 4,570,078 A 2/1986 Yashima et al.
 4,571,844 A 2/1986 Komazaku et al.
 4,624,469 A 11/1986 Bourne, Jr.
 4,634,142 A * 1/1987 Woods et al. 280/5.503
 4,645,230 A 2/1987 Hammons
 4,657,272 A 4/1987 Davenport
 4,685,693 A 8/1987 Vadjunec
 4,709,772 A 12/1987 Brunet
 4,716,980 A 1/1988 Butler
 4,722,547 A * 2/1988 Kishi et al. 367/96
 4,740,001 A 4/1988 Torleumke
 4,746,132 A 5/1988 Eagan
 4,749,210 A * 6/1988 Sugawara 280/5.519
 4,770,410 A 9/1988 Brown
 4,786,069 A 11/1988 Tang
 4,790,400 A 12/1988 Sheeter
 4,790,548 A 12/1988 Decelles et al.
 4,794,999 A 1/1989 Hester
 4,798,255 A 1/1989 Wu
 4,802,542 A 2/1989 Houston et al.
 4,809,804 A 3/1989 Houston et al.
 4,834,200 A 5/1989 Kajita
 4,863,182 A 9/1989 Chern
 4,867,188 A 9/1989 Reid
 4,869,279 A 9/1989 Hedges
 4,874,055 A 10/1989 Beer
 4,890,853 A 1/1990 Olson
 4,919,225 A 4/1990 Sturges
 4,953,851 A 9/1990 Sherlock et al.
 4,984,754 A 1/1991 Yarrington
 4,985,947 A 1/1991 Ethridge
 4,998,596 A 3/1991 Miksitz
 5,002,295 A 3/1991 Lin
 5,011,170 A 4/1991 Forbes et al.
 5,011,171 A 4/1991 Cook
 5,052,237 A 10/1991 Reimann
 5,064,209 A 11/1991 Kurschat
 5,111,899 A 5/1992 Reimann
 5,158,493 A 10/1992 Morgrey
 5,161,820 A 11/1992 Vollmer

5,168,947 A 12/1992 Rodenborn
 5,171,173 A 12/1992 Henderson et al.
 5,186,270 A 2/1993 West
 5,221,883 A 6/1993 Takenaka et al.
 5,240,266 A 8/1993 Kelley et al.
 5,241,875 A 9/1993 Kochanneck
 5,248,007 A 9/1993 Watkins et al.
 5,314,034 A 5/1994 Chittal
 5,350,033 A 9/1994 Kraft
 5,366,036 A 11/1994 Perry
 5,376,868 A 12/1994 Toyoda et al.
 5,419,624 A 5/1995 Adler et al.
 5,497,325 A * 3/1996 Mine 701/38
 5,641,173 A 6/1997 Cobb
 5,655,615 A 8/1997 Mick
 5,696,515 A 12/1997 Zyren et al.
 5,701,965 A 12/1997 Kamen et al.
 5,701,968 A 12/1997 Wright-Ott et al.
 5,718,534 A 2/1998 Neuling
 5,775,452 A 7/1998 Patmont
 5,791,425 A * 8/1998 Kamen et al. 180/7.1
 5,794,730 A 8/1998 Kamen
 5,873,582 A 2/1999 Kauffman et al.
 5,899,284 A 5/1999 Reimers et al.
 5,921,844 A 7/1999 Hollick
 5,947,505 A 9/1999 Martin
 5,971,091 A 10/1999 Kamen et al.
 5,973,463 A 10/1999 Okuda et al.
 5,975,225 A 11/1999 Kamen et al.
 5,986,221 A 11/1999 Stanley
 6,003,624 A 12/1999 Jorgensen et al.
 6,039,142 A 3/2000 Eckstein et al.
 6,050,357 A 4/2000 Staelin et al.
 6,059,062 A 5/2000 Staelin et al.
 6,125,957 A 10/2000 Kauffmann
 6,131,057 A 10/2000 Tamaki et al.
 6,223,104 B1 4/2001 Kamen et al.
 6,223,114 B1 4/2001 Boros et al.
 6,225,977 B1 5/2001 Li
 6,288,505 B1 9/2001 Heinzmann et al.
 6,302,230 B1 10/2001 Kamen et al.
 6,556,908 B1 * 4/2003 Lu et al. 701/38
 2002/0063006 A1 5/2002 Amesbury et al.

FOREIGN PATENT DOCUMENTS

DE 31 28 112 A1 2/1983
 DE 32 42 880 A1 6/1983
 DE 3411489 A1 10/1984
 DE 44 04 594 A1 8/1995
 DE 44 08 775 9/1995
 DE 196 25 498 C1 11/1997
 DE 298 08 091 U1 10/1998
 DE 298 08 096 U1 10/1998
 EP 0 109 927 7/1984
 EP 0 193 473 9/1986
 EP 0 537 698 A1 4/1993
 EP 0663 313 7/1995
 EP 0 958 978 A2 11/1999
 EP 0 551 986 A 10/2001
 FR 980 237 5/1951
 FR 2 502 090 9/1982
 GB 152664 2/1922
 GB 1213930 11/1970
 GB 2 139 576 A 11/1984
 GB 2 358 163 A 1/2000
 JP 52-44933 10/1975
 JP 57-87766 6/1982
 JP 57-110569 9/1982
 JP 59-73372 4/1984
 JP 62-12810 4/1985
 JP 0255580 12/1985
 JP 61-31685 2/1986

JP	63-305082	12/1988
JP	2-190277	7/1990
JP	4-201793	7/1992
JP	6-171562	12/1992
JP	5-213240	8/1993
JP	6-105415	12/1994
JP	7255780	3/1995
JP	10023613	7/1996
WO	WO 86/05752	10/1986
WO	WO 89/06117	7/1989
WO	WO 96/23478	8/1996
WO	WO 98/46474	10/1998
WO	WO 00/73101	12/2000
WO	WO 00 75001	12/2001

OTHER PUBLICATIONS

Schoonwinkel, A., *Design and Test of a Computer-Stabilized Unicycle*, Stanford University (1988), UMI Dissertation Services.

Vos, D., *Dynamics and Nonlinear Adaptive Control of an Autonomous Unicycle*, Massachusetts Institute of Technology, 1989.

Vos, D., *Nonlinear Control of an Autonomous Unicycle Robot: Practical Issues*, Massachusetts Institute of Technology, 1992.

Koyanagi et al., A Wheeled Inverse Pendulum Type Self-Contained Mobile Robot and its Posture Control and Vehicle Control, *The Society of Instrument and Control Engineers*, Special issue of the 31st SICE Annual Conference, Japan 1992, pp. 13-16.

Koyanagi et al., A Wheeled Inverse Pendulum Type Self-Contained Mobile Robot, *The Society of Instrument and Control Engineers*, Special issue of the 31st SICE Annual Conference, Japan 1992, pp. 51-56.

Koyanagi et al., A Wheeled Inverse Pendulum Type Self-Contained Mobile Robot and its Two Dimensional Trajectory Control, *Proceeding of the Second International Symposium on Measurement and Control in Robotics*, Japan 1992, pp. 891-898.

Watson Industries, Inc., Vertical Reference Manual ADS-C132-1A, 1992, pp. 3-4.

News article *Amazing Wheelchair Goes Up and Down Stairs*.

Osaka et al., *Stabilization of unicycle*, *Systems and Control*, vol. 25, No. 3, Japan 1981, pp. 159-166 (Abstract Only).

Roy et al., Five-Wheel Unicycle System, *Medical & Biological Engineering & Computing*, vol. 23, No. 6, United Kingdom 1985, pp. 593-596.

Kawaji, S., Stabilization of Unicycle Using Spinning Motion, *Denki Gakkai Ronbunshi, D*, vol. 107, Issue 1, Japan 1987, pp. 21-28 (Abstract Only).

Schoonwinkel, A., Design and Test of a Computer-Stabilized Unicycle, *Dissertation Abstracts International*, vol. 49/03-B, Stanford University 1988, pp. 890-1294 (Abstract only).

Vos et al., Dynamics and Nonlinear Adaptive Control of an Autonomous Unicycle—Theory and Experiment, *American Institute of Aeronautics and Astronautics*, A90-26772 10-39, Washington, D.C. 1990, pp. 487-494 (Abstract only).

TECKNICO'S Home Page, *Those Amazing Flying Machines*, <http://www.swiftsite.com/technico>.

Stew's Hovercraft Page, <http://www.stewcam.com/hovercraft.html>.

Kanoh, Adaptive Control of Inverted Pendulum, *Computrol*, vol. 2, (1983), pp. 69-75.

Yamafuji, A Proposal for Modular-Structured Mobile Robots for Work that Principally Involve a Vehicle with Two Parallel Wheels, *Automation Technology*, vol. 20, pp. 113-118 (1988).

Yamafuji & Kawamura, Study of Postural and Driving Control of Coaxial Bicycle, *Paper Read at Meeting of Japan Society of Mechanical Engineering (Series C)*, vol. 54, No. 501, (May 1988), pp. 1114-1121.

Yamafuji et al., *Synchronous Steering Control of a Parallel Bicycle*, *Paper Read at Meeting of Japan Society of Mechanical Engineering (Series C)*, vol. 55, No. 513, (May 1989), pp. 1229-1234.

Momomi & Yamafuji, Motion Control of the Parallel Bicycle-Type Mobile Robot Composed of a Triple Inverted Pendulum, *Paper Read at Meeting of Japan Society of Mechanical Engineering (Series C)*, vol. 57, No. 541 (Sep. 1991), pp. 154-159.

Popular Science, Nov. 2002, pp. 52-53 a copy off of <http://www.popsci/auto/article/0,12543,384518-2,00.html>.

Umea Institute of Design Degree Show 2002, Car Design News, <http://www.carsugbbews.cin/features/2002/020804umea-show/>.

International Search Report of Nov. 26, 2003.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

1

CONTROL OF A TRANSPORTER BASED ON ATTITUDE**CROSS REFERENCE TO RELATED APPLICATIONS**

This application claims priority from U.S. provisional patent application Ser. No. 60/395,589, filed Jul. 12, 2002, entitled "Control of Transporter Based on Attitude," which is hereby incorporated by reference, in its entirety.

TECHNICAL FIELD

The present invention pertains to transporters and methods for transporting a load, which may be a living subject, and more particularly to controlling motion of a transporter.

BACKGROUND ART

A wide range of vehicles having a motorized drive arrangement are known for conveying various subjects, either for purposive locomotion or for recreational purposes. The means used to command the motorized drive arrangement of these vehicles varies greatly. For example, an operator may manipulate an accelerator pedal to control forward motion of an automobile, while steering is typically performed using a steering wheel. Or the motion of a sporting vehicle may be controlled by rocking a foot board upon which a user is balanced towards the front or rear to mechanically move a throttle cable, as described in U.S. Pat. No. 4,790,548 (Francken). Based on the operator's physical attributes for example, or the transporter's intended functionality, alternative methods for controlling motion of a transporter may be desirable.

SUMMARY OF THE INVENTION

In a first embodiment of the invention there is provided a transporter for transporting a load over a surface. The transporter includes a support platform for supporting the load. The support platform is characterized by a fore-aft axis, a lateral axis, and an orientation with respect to the surface, the orientation referred to as an attitude. At least one ground-contacting element, which is driven by a motorized drive arrangement, is coupled to the support platform in such a manner that the attitude of the support platform is capable of variation. A sensor module generates a signal characterizing the attitude of the support platform. Based on the attitude, a controller commands the motorized drive arrangement.

In accordance with related embodiments of the invention, one or more ground-contacting elements may be flexibly coupled to the support platform in such a manner that the attitude of the support platform is capable of variation based on a position of a center of mass of the load relative to the at least one ground-contacting element.

The sensor module may include at least one distance sensor for measuring a distance characteristic of the attitude of the platform. The distance sensor may be selected from the group of distance sensors consisting of an ultrasonic distance sensor, an acoustic distance sensor, a radar distance sensor, optical distance sensor, and a contact sensor, such as a whisker(s). The at least one distance sensor may sense the distance between a fiducial point on the platform and a position on the surface disposed at a specified angle with respect to the support platform. In other embodiments, the transporter may include a first component that remains in a

2

substantially fixed vertical position relative to the surface, wherein the at least one distance sensor senses the distance between a fiducial point on the platform and the first component. One or more ground contacting elements may include a wheel having an axle, and the first component is fixed relative to the axle. Alternatively, and not meant to be limiting, one or more ground contacting elements may include a wheel supported by a frame, and the first component is fixed relative to the frame.

In accordance with other related embodiments of the invention, the attitude of the support platform is capable of variation based at least on a signal generated by a remote control device. The transporter may include a powered strut coupled to the platform, the powered strut capable of varying the attitude of the support platform based at least on the signal generated by the remote control device. The transporter may further include a user interface, wherein the attitude of the support platform is capable of variation based on a signal generated by the user interface. The controller may command motion of the transporter in the fore-aft plane and/or the lateral plane.

In accordance with another embodiment of the invention, a method for controlling a transporter having a support platform for supporting a load is presented. The support platform is characterized by an attitude with respect to the surface. The transporter includes at least one ground contacting elements flexibly coupled to the support platform in such a manner that the attitude of the platform is capable of variation. The transporter also includes a motorized drive arrangement for driving the at least one ground contacting elements. The method includes generating a signal characterizing an attitude of the support platform. The motorized drive arrangement is commanded based at least on the attitude.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing features of the invention will be more readily understood by reference to the following detailed description, taken with reference to the accompanying drawings, in which:

FIG. 1 depicts an embodiment of a human transporter, lacking a distinct user input device, to which the present invention may advantageously be applied;

FIG. 2 is a side view of a transporter, in accordance with an embodiment of the invention;

FIG. 3 is an expanded side view of a transporter, in accordance with an embodiment of the invention;

FIG. 4 is a side view of a transporter, in accordance with an embodiment of the invention; and

FIG. 5 is a block diagram of a controller of a transporter, in accordance with an embodiment of the invention.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

In accordance with an embodiment of the invention, FIG. 1 shows a transporter, 1 lacking a distinct input device, to which the present invention may advantageously be applied. Transporter 1 is described in detail in U.S. Pat. No. 6,302, 230, which is incorporated herein by reference in its entirety. Transporter 1 includes a support platform 11 for supporting a load, which may be a living subject 9, over the ground or other surface, such as a floor, which may be referred to herein generally as "ground". A subject, for example, may

stand or sit on support platform 11. Attached to support platform 11 may be a handlebar 12 that can be gripped when riding transporter 1.

One or more ground-contacting elements 2, 7 provide contact between support platform 11 and the ground. Ground-contacting elements 2, 7 may include, but are not limited to, arcuate members, tracks, treads, and wheels (hereinafter the term "wheel" will be used in the specification to refer to any such ground-contacting element without limitation). While the transporter 1 depicted in FIG. 1 lacks stability in its operating position unless subject to controlled balancing, the application of the present invention is specifically not limited to transporters of that sort and embodiments of the present invention may advantageously be applied to statically stable transporters as well.

Support platform 11 may be flexibly coupled to the wheels 2, 7 by various means known in the art, for example, a pivot mechanism, springs, or pneumatic pistons. In other embodiments, the wheels 2, 7 may have some compliance and serve the function of a spring. For purposes of the present description, platform 11 may be characterized by a fore-aft axis, a lateral axis, and an orientation with respect to the surface, which is referred to herein as an attitude. The fore-aft axis, X—X, is perpendicular to the wheel axis, while the lateral axis, Y—Y, is parallel to the axis of the wheels. Directions parallel to the axes X—X and Y—Y are called the fore-aft and lateral directions respectively.

Referring now to FIG. 2, which shows a transporter 10 in accordance with an embodiment of the invention, the attitude of support platform 11 may, for example, be capable of variation based on a position of a center of mass of the load relative to one or more wheels 13, 14. Alternatively, transporter 10 may include a power strut or other mechanism capable of altering the attitude of the support platform 11. The power strut may be controlled by a user interface located on transporter 10, such as a joystick or a rotatable potentiometer located on handlebar 12. In other embodiments, the power strut may also be controlled by a remote control device 37 (shown in FIG. 5), such as, but not limited to, an infrared or radio controlled remote control device.

The motion of transporter 10 is based, at least in part, on the attitude of the support platform 11. To determine the attitude of the support platform 11, transporter 10 includes a sensor module. Sensor module may include at least one distance sensor 17, 18 for measuring a distance characteristic of the attitude of the support platform 11. The distance measured may be, for example, the distance between a fiducial point on the support platform 11 and a surface 19, or alternatively, another component on transporter 10. A plurality of distances measured by the sensor module may be combined to generate at least one signal characteristic of the platform attitude.

Attitude/distance sensor may be one of many sensor types, such as, for example, an ultrasonic, optical, acoustic or radar sensor wherein a signal generated by a source is reflected back by a surface to a sensor receiver. The distance from the sensor to the surface can then be calculated based on the time (or phase) difference between when the signal was generated and when the reflected signal was received. Triangulation may be performed. In other embodiments, distance sensor can be a contact sensor(s) such as, without limitation, a whisker(s). For example, a plurality of whiskers, each having a predetermined length may be utilized, with distance determined based on which whisker bends or is otherwise activated when making contact with the surface. A single whisker may be utilized with distance determined based, at least in part, on the bending angle of the whisker.

Referring to FIG. 2, distance sensors 17, 18 sense the distance between a fiducial point on the platform and a position on the surface that is disposed at a specified angle 3, 4, with respect to the support platform. First distance sensor 17 is located at the front (fore) of platform 11 and senses a first distance 5 between platform 11 and surface 19. Second distance sensor 17 is located at the back (aft) of platform 11 and senses a second distance 6 between platform 11 and surface 19. By comparing distances 5 and 6, a signal indicative of an attitude of the platform 11, and more specifically, the inclination of the platform 11 in the fore-aft plane with respect to the surface 19, can be determined.

In another embodiment, at least one distance sensor 22 may sense the distance between a fiducial point on the transporter platform 11 and a first component 23 that remains in a substantially fixed vertical position relative to the surface 19, as shown in the expanded view of a transporter in FIG. 3. First component 23 may be, for example, a wheel axle 23 or a frame such as, without limitation, first support platform 69 in FIG. 4, that is used to support at least one wheel 63 and 64. In various embodiments, first component 23 may include a reflector for reflecting the signal generated by distance sensor 22.

FIG. 4 shows a transporter 60 that includes a first support platform 69 and a second support platform 61, in accordance with an embodiment of the invention. At least one wheel 63 and 64 provides contact between the first support platform 69 and the ground. Second support platform 61 is coupled to the first support platform 69 such that the second support platform 61 can tilt in the fore-aft plane based, for example, on a position of a center of mass of the loaded second support platform 61. Second support platform 61 may be tiltably attached to the first support platform 69 using, without limitation, springs 65 and 66 and/or a pivot mechanism 68. Similar to above-described embodiments, based on the tilting of the second support platform 61, at least one sensor 67 and 70 generates a signal indicative of the attitude of the second support platform 61. Attached to the first support platform 69 or second support platform 61 may be a handlebar 62 that can be gripped while operating the transporter 60.

A controller receives the signal characteristic of the attitude from the sensor module. Based at least on this signal, the controller implements a control algorithm to command a motorized drive arrangement so as to drive the at least one wheel. The controller may also respond to commands from other operator interfaces, such as a joystick or dial attached, for example, to handlebar.

FIG. 5 shows a controller 30 for controlling the motorized drive of the transporter, in accordance with an embodiment of the invention. Controller 30 receives an input characteristic of platform attitude from sensor module 34. Based at least on the input from the sensor module, controller 30 commands at least one motorized drive 35, 36. Controller 30 also interfaces with a user interface 31 and a wheel rotation sensor 33. User interface 31 may include, among other things, controls for turning the controller 30 on or off. When the controller 30 is turned off, the at least one wheel of the transporter may be free to move, such that the transporter acts as a typical push scooter. User interface 31 may also control a locking mechanism 32 for locking the at least one wheel.

The controller 30 includes a control algorithm to determine the amount of torque to be applied to the at least one wheel based on the sensed attitude of the support platform. The control algorithm may be configured either in design of the system or in real time, on the basis of current operating

5

mode and operating conditions as well as preferences of the user. Controller may implement the control algorithm by using a control loop. The operation of control loops is well known in the art of electromechanical engineering and is outlined, for example, in Fraser & Milne, *Electro-Mechanical Engineering*, IEEE Press (1994), particularly in Chapter 11, "Principles of Continuous Control" which is incorporated herein by reference.

As an example, and not meant to be limiting, the control algorithm may take the form:

$$\text{Torque Command to Wheel} = K/\theta + O/$$

where

K=gain,

θ =support platform attitude, and

O=offset.

The support platform attitude, θ , may be in the form of an error term defined as the desired support platform attitude minus the measured support platform attitude. The gain, K, may be a predetermined constant, or may be entered/adjusted by the operator through user interface 31. Responsiveness of the transporter to attitude changes can be governed by K. For example, if K is increased, a rider will perceive a stiffer response in that a small change in platform attitude will result in a large torque command. Offset, O, may be incorporated into the control algorithm to govern the torque applied to the motorized drive, either in addition to, or separate from, the direct effect of θ . Thus, for example, the user may provide an input by means of a user interface of any sort, the input being treated by the control system equivalently to a change, for example, in platform attitude.

Thus, referring back to FIG. 2, motion of the transporter 10 may be controlled by a subject changing the attitude of the platform 11. This change in attitude is reflected by distances 5, 6 sensed by the sensor module. Depending on the control algorithm, an initial change in attitude, such that first distance 5 is less than second distance 6, may result in positive torque being applied to one or more wheels 23, 24, causing the wheels 23, 24 to move forward. Likewise, an initial change in the attitude, such that first distance 5 is greater than second distance 6 may result in a negative torque applied to one or more wheels 23, 24, causing the wheels 23, 24 to move in the aft direction. If the subject then remains in his changed position on the platform such that the platform attitude remains the same, the motor will continue to torque at approximately the same rate.

In various embodiments of the invention, the sensor module may sense changes in platform attitude in addition to, or instead of inclination of support platform in the fore-aft plane. For example, sensor module may provide an attitude signal indicative of inclination of the support platform in the lateral plane relative to the surface. This may be accomplished by the use of two laterally disposed distance sensors. Changes in the angle of inclination of the support platform in the lateral plane can then be used either separately or in combination with other attitude changes to control motion of the transporter. For example, changes in the angle of inclination in the fore-aft plane can be used to control fore-aft motion, while changes in the angle of inclination in the lateral plane can be used to control steering of the transporter.

Steering may be accomplished, in an embodiment having at least two laterally disposed wheels (i.e., a left and right wheel), by providing separate motors for left and right wheels. Torque desired for the left motor and the torque desired from the right motor can be calculated separately.

6

Additionally, tracking both the left wheel motion and the right wheel motion permits adjustments to be made, as known to persons of ordinary skill in the control arts, to prevent unwanted turning of the vehicle and to account for performance variations between the two motors.

The described embodiments of the invention are intended to be merely exemplary and numerous variations and modifications will be apparent to those skilled in the art. All such variations and modifications are intended to be within the scope of the present invention as defined in the appended claims.

What is claimed is:

1. A transporter for transporting a load over a surface, the transporter comprising:

a support platform for supporting the load, the support platform characterized by a fore-aft axis and a lateral axis;

at least one ground-contacting element coupled to the support platform in such a manner that the orientation of the support platform with respect to the surface beneath and in contact with the at least one ground-contacting elements is capable of variation, the orientation referred to as an attitude;

a motorized drive arrangement for driving the at least one ground-contacting elements;

a sensor module for generating a signal characterizing the attitude of the support platform wherein the sensor module includes at least one distance sensor for measuring a distance characteristic of the attitude of the platform; and

a controller for commanding the motorized drive arrangement to apply a torque to one or more of the ground-contacting elements as a function of the attitude of the support platform based upon the signal generated by the sensor module.

2. The transporter according to claim 1, wherein one or more ground-contacting elements are flexibly coupled to the support platform in such a manner that the attitude of the support platform is capable of variation based on a position of a center of mass of the load relative to the at least one ground-contacting element.

3. The transporter according to claim 1, wherein the at least one distance sensor senses the distance between a fiducial point on the platform and a position on the surface disposed at a specified angle with respect to the support platform.

4. The transporter according to claim 1, further including a first component that remains in a substantially fixed vertical position relative to the surface, wherein the at least one distance sensor senses the distance between a fiducial point on the platform and the first component.

5. The transporter according to claim 4, wherein one or more ground contacting elements include a wheel having an axle, and the first component is fixed relative to the axle.

6. The transporter according to claim 4, wherein one or more ground contacting elements include a wheel supported by a frame, and the first component is fixed relative to the frame.

7. The transporter according to claim 1, wherein the distance sensor is selected from the group of distance sensors consisting of an ultrasonic distance sensor, an acoustic distance sensor, a radar distance sensor, a contact sensor, and an optical distance sensor.

8. The transporter according to claim 1, wherein the attitude of the support platform is capable of variation based at least on a signal generated by a remote control device.

7

9. The transporter according to claim 8, further including a powered strut coupled to the platform, the powered strut capable of varying the attitude of the support platform based at least on the signal generated by the remote control device.

10. The transporter according to claim 1, further comprising a user interface, wherein the attitude of the support platform is capable of variation based on a signal generated by the user interface.

11. The transporter according to claim 1, wherein the controller commands motion in the fore-aft plane.

12. The transporter according to claim 1, wherein the controller commands motion in the lateral plane.

13. A method for controlling a transporter having a support platform for supporting a load, the support platform characterized by an attitude with respect to the surface beneath the transporter, the transporter including at least one ground contacting elements flexibly coupled to the support platform in such a manner that the attitude of the platform is capable of variation, the transporter further including a motorized drive arrangement for driving the at least one ground contacting element, the method comprising:

generating a signal characterizing an attitude of the support platform wherein generating the signal includes measuring a distance characteristic of the attitude of the platform; and

8

commanding the motorized drive arrangement to apply a torque to one or more of the ground-contacting elements as a function of the attitude based upon the signal.

14. A method according to claim 13, wherein generating the signal includes measuring a distance between a fiducial point on the platform and a position on the surface disposed at a specified angle.

15. A method according to claim 13, wherein generating the signal includes measuring a distance between a fiducial point on the platform and a component on the transporter that remains in a substantially fixed position relative to the surface.

16. A method according to claim 13, further comprising altering the attitude of the support platform by changing a position of a center-of-mass of the load relative to the at least one ground contacting element.

17. A method according to claim 13, further comprising altering the attitude of the support platform based at least on a signal generated by a user interface of the transporter.

18. A method according to claim 13, further comprising altering the attitude of the support platform based at least on a signal generated by a remote control device.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,210,544 B2
APPLICATION NO. : 10/617598
DATED : May 1, 2007
INVENTOR(S) : Dean L. Kamen et al.

Page 1 of 1


It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In Col. 7, line 15
replace "the"
with --a.--

In Col. 8, line 2
replace "torrqe"
with --torque.--

Signed and Sealed this

Twenty-sixth Day of June, 2007

A handwritten signature in black ink, reading "Jon W. Dudas", is written over a rectangular area with a light gray dot grid background.

JON W. DUDAS

Director of the United States Patent and Trademark Office